

100WR 200WR 300WR

Wrap Around



Features

Housing

Die-formed Cold-rolled Steel

Optical

Shade: Prismatic Acrylic

Electrical

Lamp

Integrated Linear LED Module or DLC Listed T8 LED Tube

Certification

UL/cUL, ETL/cETL Listed



Integrated LED Strips Type

Model	Input Voltage	Input Wattage	Lumen (TYP)	LED CT	CRI	Dimension (L X W X H)	DLC
200WRD1-36W-4000K	120V ~ 277V	38W	3600	4000K	80	49.5" x 8.8" x 2.5"	Yes
200WRD1-36W-5000K	120V ~ 277V	38W	3780	5000K	80	49.5" x 8.8" x 2.5"	Yes
300WRD1-50W-4000K	120V ~ 277V	50W	5000	4000K	80	49.0" x 11.2" x 2.5"	
300WRD1-50W-5000K	120V ~ 277V	50W	5250	5000K	80	49.0" x 11.2" x 2.5"	
300WRD1-72W-4000K	120V ~ 277V	76W	7200	4000K	80	49.0" x 11.2" x 2.5"	
300WRD1-72W-5000K	120V ~ 277V	76W	7560	5000K	80	49.0" x 11.2" x 2.5"	

Bi-Level Dimming with Built-in Sensor

Model	Input Voltage	Input Wattage	Lumen (TYP)	Sensor	Dimming Level	Dimension (L X W X H)
200WRD1-DIM	120V ~ 277V	36W	3200	PIR Sensor	Dimming down to 10% ~50%	49.5" x 8.8" x 2.5"

Built-in Emergency Battery Back Up Type

Model	Input Voltage	Input Wattage	Lumen (TYP)	Battery	Dimension (L X W X H)
200WRD1-EM	120V ~ 277V	36W	3200	8W	49.5" x 8.8" x 2.5"

100WR 200WR 300WR

Wrap Around



DLC Listed T8 LED Tube Type

Model	Input Voltage	Input Wattage	T8 LED Tube	Lumen (TYP)	LED CT/CRI	Dimension (L X W X H)
100WRD-36W	120V ~ 277V	36W	2 x 18W	4000	4000K or 5000K / > 80	49.0" x 6.5" x 2.5"
200WRD-36W	120V ~ 277V	36W	2 x 18W	4000	4000K or 5000K / > 80	49.5" x 8.8" x 2.5"
300WRD-72W	120V ~ 277V	72W	4 x 18W	8000	4000K or 5000K / > 80	49.0" x 11.2" x 2.5"

T8 Lamp Type

Model	Input Voltage	Input Wattage	Lamp	Dimension (L X W X H)
100WR	120V ~ 277V	58W	2 x F32T8, 32W	49.0" x 6.5" x 2.5"
200WR	120V ~ 277V	58W	2 x F32T8, 32W	49.5" x 8.8" x 2.5"
300WR	120V ~ 277V	106W	4 x F32T8, 32W	49.0" x 11.2" x 2.5"