

# 1015

## Ceiling Fixture



### Features

#### Housing

Die-formed Cold-rolled Steel  
 Finish Option: -06 White, -30 Oil Rubbed Bronze, -62 Satin Nickel

#### Optical

Shade Option: -AG Alabaster Shade(13.5" x 6.5"), -FG Frosted Glass (13.5" x 7.4")

#### Electrical

High Power Factor, Low THD

#### Lamp


LED Type: Built-in (Color Temperature Option – 3000K, 3500K, 4000K, 5000K)  
 CFL Type: GU24 CFL Bulb (Color Temperature Option – 2700K, 4000K)

#### Certification

UL/cUL or ETL/cETL Listed, Suitable for Damp Locations

#### Warranty

5 Years Warranty on Driver and LED Module



### LED Type

Model	Input Voltage	Input Wattage	LED CT / CRI	Lumen (TYP)	Dimension (OD X H)	Finish	Shade	Energy Star
1015D-xxxxK-62	120V	18W	3000K / 80	1520	13.5" x 7.4"	Satin Nickel	Acrylic	Yes

### GU24 CFL Type

Model	Input Voltage	Input Wattage	Lamp	Finish	Shade	Dimension (OD x H)	Energy Star
1015PG-218-62	120V	36W	2 x 18W GU24	Satin Nickel	Frosted or Alabaster Glass	13.0" x 6.5"	---
1015PG-223-62	120V	46W	2 x 23W GU24	Satin Nickel	Frosted or Alabaster Glass	13.0" x 6.5"	---