

150WRD

LED Wrap Around



Features

Housing

Die-formed Cold-rolled Steel

Optical

Shade: Prismatic Acrylic

Electrical

High Power Factor, Low THD

Lamp

Integrated Linear LED Module

Certification

ETL/cETL Listed, Suitable for Damp Locations



Integrated LED Strips Type

| Model | Input Voltage | Input Wattage | Lumen (TYP) | LED CT | CRI | Dimension (L X W X H) | DLC Premium |
|----------------|---------------|---------------|-------------|--------|-----|-----------------------|-------------|
| 150WRD-40W-830 | 120V ~ 277V | 36W | 4757 | 3000K | 80 | 46.5" x 4.12" x 3.64" | Yes |
| 150WRD-40W-840 | 120V ~ 277V | 36W | 4680 | 4000K | 80 | 46.5" x 4.12" x 3.64" | Yes |
| 150WRD-40W-850 | 120V ~ 277V | 36W | 4680 | 5000K | 80 | 46.5" x 4.12" x 3.64" | Yes |

Bi-Level Dimming with Built-in Sensor

| Model | Input Voltage | Input Wattage | Lumen (TYP) | LED CT | CRI | Dimension (L X W X H) |
|-----------|---------------|---------------|-------------|--------|-----|-----------------------|
| 150WRD-BI | 120V ~ 277V | 36W | 4757 | 3000K | 80 | 46.5" x 4.12" x 3.64" |

Built-in Emergency Battery Back Up Type

| Model | Input Voltage | Input Wattage | Lumen (TYP) | LED CT / CRI | Dimension (L X W X H) |
|-----------|---------------|---------------|-------------|--------------|-----------------------|
| 150WRD-EM | 120V ~ 277V | 36W | 4757 | 3000K / 80 | 46.5" x 4.12" x 3.64" |