

150WRD

LED Wrap Around



Features

Housing

Die-formed Cold-rolled Steel

Optical

Shade: Prismatic Acrylic

Electrical

High Power Factor, Low THD

Lamp

Integrated Linear LED Module

Certification

ETL/cETL Listed, Suitable for Damp Locations



Integrated LED Strips Type

Model	Input Voltage	Input Wattage	Lumen (TYP)	LED CT	CRI	Dimension (L X W X H)
150WRD-40W-830	120V ~ 277V	36W	4680	3000K	80	46.5" x 4.12" x 3.64"
150WRD-40W-840	120V ~ 277V	36W	4680	4000K	80	46.5" x 4.12" x 3.64"
150WRD-40W-850	120V ~ 277V	36W	4680	5000K	80	46.5" x 4.12" x 3.64"

Bi-Level Dimming with Built-in Sensor

Model	Input Voltage	Input Wattage	Lumen (TYP)	LED CT	CRI	Dimension (L X W X H)
150WRD-BI	120V ~ 277V	36W	4680	3000K	80	46.5" x 4.12" x 3.64"

Built-in Emergency Battery Back Up Type

Model	Input Voltage	Input Wattage	Lumen (TYP)	LED CT / CRI	Dimension (L X W X H)
150WRD-EM	120V ~ 277V	36W	4680	3000K / 80	46.5" x 4.12" x 3.64"