

Features

Housing

Die-formed Cold-rolled Steel
Finish Options: -30 Oil Rubbed Bronze, -06 White, -62 Satin Nickel

Optical

Shade: High Transmission Acrylic Create Excellent Light Distribution and Uniformity
LED: High Efficiency, High CRI, Binned and Mixed to Reach Uniform Light

Electrical

High Power Factor, Low THD

Lamp

Built-in LED Module
MCT Type: Get Preferable Fixture Color Temperature by Slide Switch on LED Board
Color Temperature Option – 3000K, 3500K, 4000K

Certifications

ETL/cETL Listed

Warranty

5 Years Warranty on Driver and LED Module



LED Type

Model	Input Voltage	Input Voltage	LED CT	Lumen (Typ)	Finish	Dimension (OD X H)	Energy Star
2-0245D-A-xxxxK	120V	17W	3000K / 3500K / 4000K / 5000K	1600	White	11.0" x 3.3"	Yes
2-0246D-A-xxxxK	120V ~ 277V	24W	3000K / 3500K / 4000K / 5000K	2560	White	14.0" x 3.6"	Yes
2-0240D-06-xxxxK	120V	12W	3000K or 4000K	780	White	11.0" x 3.3"	---
2-0241D-MCT-06	120V	25W	3000K, 3500K, 4000K	1670	White	14.0" x 3.6"	---
2-0242D-MCT-06	120V	25W	3000K, 3500K, 4000K	1520	White	16.0" x 4.0"	---