

2-0245-A-BI-EM 2-0246-A-BI-EM



Round Puff Ceiling Fixture

Features

Housing

Die-formed Cold-rolled Steel

Optical

Shade: High Transmission Acrylic Create Excellent Light Distribution and Uniformity

LED: High Efficiency, High CRI, Binned and Mixed to Reach Uniform Light

Electrical

High Power Factor, Low THD

Built-in Emergency Lighting

Bi-Level Lighting

Lamp

LED Type: Built-in

Certifications

ETL/cETL Listed, Energy Star

Warranty

5 Years Warranty on Driver and LED Module



Emergency Backup Models

Model	Input Voltage	Input Voltage	LED CT	CRI	Lumen (Typ)	Dimension (OD X H)	Energy Star
2-0245D-A-3000K-EM	120V ~ 277V	18W	3000K	> 80	1600	11.0" x 3.5"	Yes
2-0245D-A-4000K-EM	120V ~ 277V	18W	4000K	> 80	1680	11.0" x 3.5"	Yes
2-0246D-A-3000K-EM	120V ~ 277V	24W	3000K	> 80	2050	14.0" x 3.5"	Yes
2-0246D-A-4000K-EM	120V ~ 277V	24W	4000K	> 80	2160	14.0" x 3.5"	Yes

Bi-Level Lights with Built-in High Frequency Sensor

Model	Input Voltage	Input Voltage	LED CT	CRI	Lumen (Typ)	Dimension (OD X H)	Energy Star
2-0245D-A-3000K-BI	120V ~ 277V	18W	3000K	> 80	1600	11.0" x 3.5"	Yes
2-0245D-A-4000K-BI	120V ~ 277V	18W	4000K	> 80	1680	11.0" x 3.5"	Yes
2-0246D-A-3000K-BI	120V ~ 277V	24W	3000K	> 80	2050	14.0" x 3.5"	Yes
2-0246D-A-4000K-BI	120V ~ 277V	24W	4000K	> 80	2160	14.0" x 3.5"	Yes

Bi-Level Lights with Emergency Backup

Model	Input Voltage	Input Voltage	LED CT	CRI	Lumen (Typ)	Dimension (OD X H)	Energy Star
2-0245D-A-3000K-BI-EM	120V ~ 277V	18W	3000K	> 80	1600	11.0" x 3.5"	Yes
2-0245D-A-4000K-BI-EM	120V ~ 277V	18W	4000K	> 80	1680	11.0" x 3.5"	Yes
2-0246D-A-3000K-BI-EM	120V ~ 277V	24W	3000K	> 80	2050	14.0" x 3.5"	Yes
2-0246D-A-4000K-BI-EM	120V ~ 277V	24W	4000K	> 80	2160	14.0" x 3.5"	Yes