

# 2-0245-A-EM 2-0246-A-EM

Round Puff Ceiling Fixture



## Features

### Housing

Die-formed Cold-rolled Steel

### Optical

Shade: High Transmission Acrylic Create Excellent Light Distribution and Uniformity

### Electrical

LED Driver: 120V Dimming Type or 120V - 277V Constant Current Type,  
High Power Factor, Low THD

*EM: Built-in Emergency Lighting with 8W Battery Pack*

*HFSR: Built-in HF Sensor on/off or Bi-level Dimming*

*Bi: Bi-Level Lighting*

### Lamp

LED Type: Built-in, 50,000 hours Rating

Color Temperature Options: 3000K, 3500K, 4000K or 5000K

### Certifications

ETL/cETL Listed

### Warranty

5 Years Warranty on Driver and LED Module



## Emergency Backup Models

Model	Input Voltage	Input Voltage	LED CT	CRI	Lumen (Typ)	Dimension (OD X H)	Energy Star
2-0245D-A-3000K-EM	120V	18W	3000K	> 80	1340	11.0" x 4.8"	Yes
2-0245D-A-4000K-EM	120V	18W	4000K	> 80	1400	11.0" x 4.8"	Yes
2-0246D-A-3000K-EM	120V ~ 277V	24W	3000K	> 80	2000	14.0" x 5.0"	Yes
2-0246D-A-4000K-EM	120V ~ 277V	24W	4000K	> 80	2100	14.0" x 5.0"	Yes

## Emergency Backup Lights with Built-in High Frequency Sensor

Model	Input Voltage	Input Voltage	LED CT	CRI	Lumen (Typ)	Dimension (OD X H)	Energy Star
2-0245D-A-3000K-EM-HFSR	120V	18W	3000K	> 80	1340	11.0" x 4.8"	Yes
2-0245D-A-4000K-EM-HFSR	120V	18W	4000K	> 80	1400	11.0" x 4.8"	Yes
2-0246D-A-3000K-EM-HFSR	120V ~ 277V	24W	3000K	> 80	2000	14.0" x 5.0"	Yes
2-0246D-A-4000K-EM-HFSR	120V ~ 277V	24W	4000K	> 80	2100	14.0" x 5.0"	Yes

## Emergency Backup Lights with Built-in High Frequency Sensor and Bi-Level Dimming

Model	Input Voltage	Input Voltage	LED CT	CRI	Lumen (Typ)	Dimension (OD X H)	Energy Star
2-0245D-A-3000K-EM-HFSR-BI	120V	18W	3000K	> 80	1340	11.0" x 4.8"	Yes
2-0245D-A-4000K-EM-HFSR-BI	120V	18W	4000K	> 80	1400	11.0" x 4.8"	Yes
2-0246D-A-3000K-EM-HFSR-BI	120V ~ 277V	24W	3000K	> 80	2000	14.0" x 5.0"	Yes
2-0246D-A-4000K-EM-HFSR-BI	120V ~ 277V	24W	4000K	> 80	2100	14.0" x 5.0"	Yes