

# 2-0245 2-0246 2-0247

## Round Puff Ceiling Fixture



### Features

#### Housing

Die-formed Cold-rolled Steel

#### Optical

Shade: High Transmission Acrylic Create Excellent Light Distribution and Uniformity

LED: High Efficiency, High CRI, Binned and Mixed to Reach Uniform Light

#### Electrical

High Power Factor, Low THD

#### Lamp

LED Type: Built-in (More Color Temperature Option – 3500K, 5000K)


CFL Type: T9 Circline or GU24 CFL Lamp (More Color Temperature Option – 2700K, 4000K)

#### Certifications

UL/cUL, ETL/cETL Listed, Suitable for Damp Locations

#### Warranty

5 Years Warranty on Driver and LED Module



### LED Type

Model	Input Voltage	Input Voltage	LED CT/CRI	Lumen (Typ)	Dimension (OD X H)	Energy Star
2-0245D-3000K	120V	18W	3000K / 80	1340	11.0" x 4.3"	Yes
2-0245D-4100K	120V	18W	4100K / 80	1400	11.0" x 4.3"	Yes
2-0246D-3000K	120V ~ 277V	24W	3000K / 80	2000	14.0" x 4.5"	Yes
2-0246D-4100K	120V ~ 277V	24W	4100K / 80	2100	14.0" x 4.5"	Yes
2-0247D-3000K	120V ~ 277V	35W	3000K / 80	2800	18.9" x 4.5"	
2-0247D-4100K	120V ~ 277V	35W	4100K / 80	2900	18.9" x 4.5"	

### CFL Type

Model	Input Voltage	Shade	Lamp	Dimension (OD X H)	Energy Star
2-0245PG-123	120V	Opal Acrylic	1 x 23W GU24	11.0" x 4.3"	
2-0246PG-213	120V	Opal Acrylic	2 x 13W GU24	14.0" x 4.5"	
2-0247-2232	120V	Opal Acrylic	22W+32W T9 Cir.	18.9" x 4.5"	