

2-0345 2-0346 2-0347

Square Puff Ceiling Fixture



Features

Housing

Die-formed Cold-rolled Steel

Optical

Shade: High Transmission Acrylic Create Excellent Light Distribution and Uniformity

LED: High Efficiency, High CRI, Binned and Mixed to Reach Uniform Light

Electrical

High Power Factor, Low THD

Lamp

LED Type: Built-in (More Color Temperature Option – 3500K, 4000K, 5000K)


CFL Type: GU24 CFL Lamp (Color Temperature Option – 2700K, 4000K)

Certifications

UL/cUL or ETL/cETL Listed, Suitable for Damp Locations

Warranty

5 Years Warranty on Driver and LED Module



LED Type

| Model | Input Voltage | Input Wattage | LED CT | CRI | Lumen (Typ) | Dimension (L X W X H) | Energy Star |
|---------------|---------------|---------------|--------|------|-------------|-----------------------|-------------|
| 2-0345D-xxxxK | 120V | 17W | 3000K | > 80 | 1590 | 11.0" x 11.0" x 3.2" | Yes |
| 2-0346D-xxxxK | 120V ~ 277V | 24W | 3000K | > 80 | 2384 | 14.0" x 14.0" x 3.4" | Yes |
| 2-0347D-xxxxK | 120V ~ 277V | 35W | 3000K | > 80 | 3250 | 19.0" x 19.0" x 3.8" | Yes |

CFL Type

| Model | Input Voltage | Input Wattage | Shade | Lamp | Dimension (L X W X H) | Energy Star |
|--------------|---------------|---------------|--------------|--------------|-----------------------|-------------|
| 2-0345PG-123 | 120V | 23W | Opal Acrylic | 1 x 23W GU24 | 11.0" x 11.0" x 3.2" | |
| 2-0346PG-213 | 120V | 26W | Opal Acrylic | 2 x 13W GU24 | 14.0" x 14.0" x 3.4" | |
| 2-0347PG-318 | 120V | 54W | Opal Acrylic | 3 x 18W GU24 | 19.0" x 19.0" x 3.8" | |