

# BH48C

## LED Vapor Tight



### Features

#### Housing

Injection Molded Polycarbonate  
Stainless Steel Mounting Brackets  
Suitable for Ceiling Mount or Hanging Mount with 3 feet Suspension Chains

#### Optical

Diffuser: Injection Molded with UV Stabilized Transparent or Opal Polycarbonate

#### Electrical

Built-in UL Approved Constant Current LED Driver

#### Lamp

Built-in LED Module  
Color Temperature Option: 3000K, 4000K, 5000K or 6400K

#### Certification

UL Listed, IP65 Rated

#### Warranty

5 Years Warranty on Driver and LED Module



### LED Type

Model	Lens	Input Voltage	Input Wattage	LED CT	CRI	Lumen (TYP)	Dimension (L X W X H)	DLC
BH48C-100W-4000K	Clear PC	120V ~ 277V	96W	4000K	>80	12800	49.8" x 9.45" x 4.33"	Standard
BH48C-100W-5000K	Clear PC	120V ~ 277V	96W	5000K	>80	12800	49.8" x 9.45" x 4.33"	Standard
BH48C-100W-6400K	Clear PC	120V ~ 277V	96W	6400K	>80	12800	49.8" x 9.45" x 4.33"	Standard
BH48F-100W-4000K	Frosted PC	120V ~ 277V	96W	4000K	>80	11000	49.8" x 9.45" x 4.33"	Standard
BH48F-100W-5000K	Frosted PC	120V ~ 277V	96W	5000K	>80	11000	49.8" x 9.45" x 4.33"	Standard
BH48F-100W-6400K	Frosted PC	120V ~ 277V	96W	6400K	>80	11000	49.8" x 9.45" x 4.33"	Standard