

LED Lighting Fixture

DC012D-2G / DC014D-2G / DC016D-2G



CEC Listed - Meets JA8 CRI >95 - Meets JA10 Flicker Free



Emergency Type - EM



Pendant Mount, - PD

- * Housing: Die-formed cold rolled steel
- * Shade: High transmission acrylic creates excellent light distribution and uniformity
- * LED Driver: 120V triac dimming type or 120V ~ 277V, 0 ~ 10V dimming type
- * Min. Dimming level: 3%
- * Power Factor: > 0.98
- * THD: < 10%
- * LM80, TM21 : 60,000 hours rating
- * LED Rated Life: > 36000 hours
- * LED CRI > 95 per JA8 Standard
- * Flicker Free: Meets JA10 standard
- * Certification: ETL / cETL, Energy Star, CEC listed
- * Warranty: 5 years
- * Color Temperature Option: 3000K or 3500K or 4000K
- * Finish: -62 Satin Nickel. -30 Oil Rubbed Bronze -06 White

Model / Order Code	Input Voltage	Input Wattage	Lumen (typ)	LED CT	CRI	Dimming	Finish	Dimensions (ODxH)
DC012D-2G-3000K (JA8)	120V	18W	1310	3000K	> 95	Triac	Satin Nickel	12.0"OD x 3.7"H
DC014D-2G-3000K (JA8)	120 ~ 277V	24W	2000	3000K	> 95	0-10V	Satin Nickel	14.5"OD x 4.5"H
DC016D-2G-3000K (JA8)	120 ~ 277V	30W	2300	3000K	> 95	0-10V	Satin Nickel	16.0"OD x 4.5"H

* Lumen data - Tested by 3000K CT



16200 S. Figueroa St., Gardena, Ca 90248
 el: 310-324-8880 e-mail: info@sunpkco.com
www.sunparkelectronics.com