

HB7D

LED High Bay



Features

Housing

Die-formed Cold-rolled Steel and V Hook & Hanging Chain Included
Eco-frame & full Body Linear Construction

Optical

High Lumen Efficiency and High CRI LED
High Transmission Acrylic Shade

Electrical

UL2459 / CSA182.3 Power Connector Included

Lamp

Integrate LED Module with High CRI
Rated 50,000 Hours LED Life

Certification

ETL/cETL Listed, Suitable for Damp Locations, DLC Listed

Warranty

5 Years Limited Warranty on Driver and LED

Options

-LS with Lens -Bi with Bi-Level Light
-EM with Emergency Driver (Built-in or External EM Driver)



DLC Standard Models

Model	Input Voltage	Input Wattage	LED CT	CRI	Lumen (TYP)	Dimension (L x W x H)	DLC
HB7D-110-HE(4000K)	120V ~ 277V	110W	4000K	80	12990	44.0" x 10.0" x 3.4"	Standard
HB7D-110-HE(5000K)	120V ~ 277V	110W	5000K	80	14680	44.0" x 10.0" x 3.4"	Standard
HB7D-160-HE(4000K)	120V ~ 277V	165W	4000K	80	19450	44.0" x 10.0" x 3.4"	Standard
HB7D-160-HE(5000K)	120V ~ 277V	165W	5000K	80	22020	44.0" x 10.0" x 3.4"	Standard

DLC Premium Models

Model	Input Voltage	Input Wattage	LED CT	CRI	Lumen (TYP)	Dimension (L x W x H)	DLC
HB7D-140-VHO-4000K	120V ~ 277V	140W	4000K	80	17830	44.0" x 10.0" x 3.4"	Premium
HB7D-140-VHO-5000K	120V ~ 277V	140W	5000K	80	18320	44.0" x 10.0" x 3.4"	Premium