

# MDF033 MDF025

## Wall Sconce



### Features

#### Housing

Die-formed Cold-rolled Steel  
 Finish Option: -62 Satin Nickel -30 Oil Rubbed Bronze

#### Optical

Shade: High Transmission Acrylic Creates Excellent Light Distribution and Uniformity  
 LED: High Efficiency, High CRI, Binned and Mixed to Reach Uniform Light

#### Electrical

High Power Factor, Low THD

**JA8 Type: High Power Factor (> 0.98), Low THD (< 10%)**  
**LED Driver, 120V-277V, 0-10V Dimming Type (Min. Dimming Level 3%)**  
**Flicker Free: Meets JA10 Standard**

#### Lamp


LED Type: Integrate LED Module, 3000K LED  
 More Color Temperature Option 3500K, 4000K, 5000K  
 GU24 Type: - CFL Bulb, 2700K or 4000K - 9W LED Bulb, 3000K or 4000K  
**JA8 Type: 3000K only, LM80/TM21 60,000hrs Min. Rating**

#### Certification

UL/cUL or ETL/cETL Listed, Suitable for Damp Locations  
**JA8 Type – CEL Listed, Meets Title24 JA8 Requirements**

#### Warranty

5 Years Limited Warranty on Driver and LED



### LED Type

Model	Input Voltage	Input Wattage	LED CT	CRI	Lumen (TYP)	Finish/Shade	Dimension (W x H X D)	Energy Star
MDF033D-14W-xxxxK	120V	14W	3000K	>80	950	Satin Nickel / Acrylic	9.4" x 10.5" x 4.0"	Yes
MDF033D-xxxxK	120V-277V	22W	3000K	>80	1800	Satin Nickel / Acrylic	9.4" x 10.5" x 4.0"	Yes

### JA8 Type

Model	Input Voltage	Input Wattage	LED CT	CRI	Lumen (TYP)	Finish/Shade	Dimension (W x H X D)	CEC T24 Listed
MDF033D(JA8)	120V-277V	22W	3000K	>90	1580	Satin Nickel / Acrylic	9.4" x 10.5" x 4.0"	Yes

### GU24 Type

Model	Input Voltage	Lamp	Finish	Shade	Dimension (W x H X D)	Energy Star
MDF033PG-213	120V	2 x 13W GU24	Satin Nickel	Acrylic	9.4" x 10.5" x 4.0"	---
MDF025PG-213	120V	2 x 13W GU24	Plastic, Silver Color	Acrylic	9.1" x 10.5" x 4.0"	---