

MDF033 MDF025

Wall Sconce



Features

Housing

Die-formed Cold-rolled Steel
 Finish Option: -62 Satin Nickel -30 Oil Rubbed Bronze

Optical

Shade: High Transmission Acrylic Creates Excellent Light Distribution and Uniformity

Electrical

High Power Factor, Low THD
 -EM: Built-in Emergency Light

JA8 Type: High Power Factor (> 0.98), Low THD (< 10%)
LED Driver, 120V-277V, 0-10V Dimming Type (Min. Dimming Level 3%)
Flicker Free: Meets JA10 Standard

Lamp

LED Type: Integrate LED Module, 3000K LED
 More Color Temperature Option 3500K, 4000K, 5000K
 GU24 Type: - CFL Bulb, 2700K or 4000K - 9W LED Bulb, 3000K or 4000K


JA8 Type: 3000K only, LM80/TM21 60,000hrs Min. Rating

Certification

UL/cUL or ETL/cETL Listed, Suitable for Damp Locations
JA8 Type – CEL Listed, Meets Title24 JA8 Requirements

Warranty

5 Years Limited Warranty on Driver and LED



LED Type

Model	Input Voltage	Input Wattage	LED CT	CRI	Lumen (TYP)	Finish/Shade	Dimension (W x H X D)	Energy Star
MDF033D-14W-xxxxK	120V	14W	3000K	>80	950	Satin Nickel / Acrylic	9.4" x 10.5" x 4.0"	Yes
MDF033D-xxxxK	120V-277V	22W	3000K	>80	1800	Satin Nickel / Acrylic	9.4" x 10.5" x 4.0"	Yes
MDF033D-EM-xxxxK	120V-277V	22W	3000K	>80	1800	Satin Nickel / Acrylic	9.4" x 10.5" x 4.0"	---

JA8 Type

Model	Input Voltage	Input Wattage	LED CT	CRI	Lumen (TYP)	Finish/Shade	Dimension (W x H X D)	CEC T24 Listed
MDF033D(JA8)	120V-277V	22W	3000K	>90	1580	Satin Nickel / Acrylic	9.4" x 10.5" x 4.0"	Yes

GU24 Type

Model	Input Voltage	Lamp	Finish	Shade	Dimension (W x H X D)	Energy Star
MDF033PG-213	120V	2 x 13W GU24	Satin Nickel	Acrylic	9.4" x 10.5" x 4.0"	---
MDF025PG-213	120V	2 x 13W GU24	Plastic, Silver Color	Acrylic	9.1" x 10.5" x 4.0"	---