

RT-24ST RT-48ST

LED Strip Re-trofit Kit



Features

Housing

Die-formed Cold-rolled Steel

Optical

Shade: High Transmission Acrylic Creates Excellent Light Distribution and Uniformity

Electrical

Re-Trofit Standard T8 Fluorescent Lamp Strip

Built-in Emergency Lighting

Bi-Level Lighting

Lamp

LED: High Efficiency, High CRI, Binned and Mixed to Reach Uniform Light

Integrate LED Module with High CRI

Certification

ETL/cETL Listed



LED Strip Re-trofit Kit

Model	Input Voltage	Input Wattage	Power Factor	THD	Lumen (TYP)	LED CT	CRI	Dimension (L X W X H)
RT-24ST-4000K	120V ~ 277V	23W	0.937	8.0%	2735	4000K	>80	24.0" x 4.4" x 1.8"
RT-24ST-5000K	120V ~ 277V	23W	0.994	8.0%	2740	5000K	>80	24.0" x 4.4" x 1.8"
RT-24ST-HE-4000K	120V ~ 277V	23W	0.928	8.729%	3200	4000K	>80	24.0" x 4.4" x 1.8"
RT-24ST-HE-5000K	120V ~ 277V	23W	0.960	9.1%	3290	5000K	>80	24.0" x 4.4" x 1.8"
RT-48ST-4000K	120V ~ 277V	44W	0.961	8.7%	5290	4000K	>80	48.0" x 4.4" x 1.8"
RT-48ST-5000K	120V ~ 277V	44W	0.993	11%	5060	5000K	>80	48.0" x 4.4" x 1.8"
RT-48ST-HE-36W-4000K	120V ~ 277V	36W	0.959	8.8%	4170	4000K	>80	48.0" x 4.4" x 1.8"
RT-48ST-HE-36W-5000K	120V ~ 277V	36W	0.992	11%	4168	5000K	>80	48.0" x 4.4" x 1.8"
RT-48ST-HE-48W-4000K	120V ~ 277V	46W	0.962	9.478%	6400	4000K	>80	48.0" x 4.4" x 1.8"
RT-48ST-HE-48W-5000K	120V ~ 277V	46W	0.960	8.7%	6570	5000K	>80	48.0" x 4.4" x 1.8"
RT-48ST-VHO-36W-4000K	120V ~ 277V	31W	0.955	10.248%	3980	4000K	>80	48.0" x 4.4" x 1.8"
RT-48ST-VHO-36W-5000K	120V ~ 277V	31W	0.950	10.25%	4000	5000K	>80	48.0" x 4.4" x 1.8"