

TP Series

LED Vapor Tight



Features

Housing

Injection Molded Polycarbonate
Suitable for Ceiling Mount or Suspended Mount

Optical

Shade: Injection Molded High Transmission Opal Polycarbonate Creates Excellent Light Distribution and Uniformity
High Luminous Efficacy > 110 lm/W

Electrical

Built-in Constant Current LED Driver with High efficient LED Module
-BI: Bi-Level Light Option

Lamp

Built-in LED Module

Certification

UL/cUL Listed, Suitable for Damp Locations, DLC Listed

Warranty

5 Years Warranty on Driver and LED Module



LED Type

| Model | Input Voltage | Input Wattage | LED CT | CRI | Lumen (TYP) | Dimension (L X W X H) | DLC |
|-----------------|---------------|---------------|--------|-----|-------------|-----------------------|-----|
| TP20W-2FT-3000K | 120V ~ 277V | 20W | 3000K | 82 | 2330 | 23.6" x 3.7" x 2.4" | Yes |
| TP20W-2FT-4000K | 120V ~ 277V | 20W | 4000K | 82 | 2330 | 23.6" x 3.7" x 2.4" | Yes |
| TP20W-2FT-5000K | 120V ~ 277V | 20W | 5000K | 82 | 2400 | 23.6" x 3.7" x 2.4" | Yes |
| TP36W-4FT-3000K | 120V ~ 277V | 36W | 3000K | 82 | 4230 | 47.2" x 3.7" x 2.4" | Yes |
| TP36W-4FT-4000K | 120V ~ 277V | 36W | 4000K | 82 | 4400 | 47.2" x 3.7" x 2.4" | Yes |
| TP36W-4FT-5000K | 120V ~ 277V | 36W | 5000K | 82 | 4600 | 47.2" x 3.7" x 2.4" | Yes |
| TP45W-4FT-3000K | 120V ~ 277V | 42.5W | 4000K | 82 | 5000 | 47.2" x 3.7" x 2.4" | Yes |
| TP45W-4FT-4000K | 120V ~ 277V | 42.5W | 4000K | 82 | 5000 | 47.2" x 3.7" x 2.4" | Yes |
| TP45W-4FT-5000K | 120V ~ 277V | 42.5W | 5000K | 82 | 5300 | 47.2" x 3.7" x 2.4" | Yes |
| TP70W-8FT-3000K | 120V ~ 277V | 70W | 4000K | 82 | 7900 | 94.5" x 3.7" x 2.4" | Yes |
| TP70W-8FT-4000K | 120V ~ 277V | 70W | 4000K | 82 | 7900 | 94.5" x 3.7" x 2.4" | Yes |
| TP70W-8FT-5000K | 120V ~ 277V | 70W | 5000K | 82 | 8400 | 94.5" x 3.7" x 2.4" | Yes |