

TRF Series

LED Troffer



Features

Housing

Die-formed Cold-rolled Steel

Optical

High Light Transmission Polycarbonate Diffuser

High Lumen Efficiency and High CRI

Electrical

120V - 277V

Lamp

Integrate LED Module with High CRI

Rated 50,000 Hours LED Life

Certification

ETL/cETL Listed

Warranty

5 Years Limited Warranty on Driver and LED



Double Basket

Model	Input Voltage	Input Wattage	LED CT	CRI	Lumen (TYP)	TYPE	Dimension (L x W x H)	DLC
TRF-2x2-40W 4000K	120V ~ 277V	36W	4000K	> 80	4000	2' x 2'	23.8" x 23.8" x4.13"	Yes
TRF-2x2-40W 5000K	120V ~ 277V	36W	5000K	> 80	4200	2' x 2'	23.8" x 23.8" x4.13"	Yes
TRF-2x4-50W 4000K	120V ~ 277V	50W	4000K	> 80	5000	2' x 4'	47.6" x 23.8" x4.13"	Yes
TRF-2x4-50W 5000K	120V ~ 277V	50W	5000K	> 80	5250	2' x 4'	47.6" x 23.8" x4.13"	Yes

Single Basket

Model	Input Voltage	Input Wattage	LED CT	CRI	Lumen (TYP)	TYPE	Dimension (L x W x H)	DLC
TRF-S-2x2-36W-4000K	120V ~ 277V	36W	4000K	> 80	4500	2' x 2'	23.8" x 23.8" x4.13"	Yes
TRF-S-2x2-36W-5000K	120V ~ 277V	36W	5000K	> 80	4720	2' x 2'	23.8" x 23.8" x4.13"	Yes
TRF-S-2x4-50W-4000K	120V ~ 277V	50W	4000K	> 80	6250	2' x 4'	47.6" x 23.8" x4.13"	Yes
TRF-S-2x4-50W-5000K	120V ~ 277V	50W	5000K	> 80	6560	2' x 4'	47.6" x 23.8" x4.13"	Yes