

# WP7-A WP8-A WP9-A

## Wall Pack, Outdoor



### Features

#### Housing

Die-formed Cold-rolled Steel with Epoxy Powder Coated Finish

#### Optical

Shade: High Transmission Acrylic Creates Excellent Light Distribution and Uniformity

LED: High Efficiency, High CRI, Binned and Mixed to Reach Uniform Light

#### Electrical

120V – 277V

#### Lamp

Integrate LED Module

More Color Temperature Option 4000K

#### Certification


ETL/cETL Listed, Suitable for Wet Locations

#### Warranty

5 Years Limited Warranty on Driver and LED

#### Options

- Bi Bi-Level Light Option
- EM Emergency Backup Light Option



### LED Type

Model	Input Voltage	Input Wattage	LED CT	Lumen (TYP)	LED (Light Source) Lumen/Wattage	Finish	Shade	Dimension (L x W X D)
WP7-A-05-18W-3000K	120V ~ 277V	15W	3000K	800	1294 lm / 14W	Black	Acrylic	13.25" x 8.25" x 4.0"
WP8-A-05-23W-3000K	120V ~ 277V	22W	3000K	1200	2255 lm / 22W	Black	Acrylic	21.7" x 8.25" x 4.0"
WP9-A-05-34W-3000K	120V ~ 277V	34W	3000K	2000	3755 lm / 34W	Black	Acrylic	30.0" x 8.25" x 4.0"