

# 3-3383

## Wall Mount / Ceiling Mount, Outdoor



### Features

#### Housing

Die-cast Aluminum with Powder Coated Finish  
 Finish Option: -06 White, -08 Gray

#### Optical

#### Electrical

120V  
 High Power Factor, Low THD

#### Lamp


LED Type: LED Module, Color Temperature Option 3000K, 3500K, 4000K, 5000K  
 GU24 CFL Bulb Type: Color Temperature Option 2700K, 4000K  
 GU24 LED Bulb: 9W, Color Temperature Option 3000K, 4000K

#### Certification

UL/cUL or ETL/cETL Listed, Suitable for Wet Locations

#### Warranty

5 Years Limited Warranty on Driver and LED



### LED Type

Model	Input Voltage	Input Wattage	LED CT/CRI	Lumen (TYP)	Finish / Shade	Dimension (H x W X E)	Energy Star
3-3383D-05-xxxxK	120V	15W	3000K / >80	850	Black / PC	11.3" x 7.0" x 3.7"	Yes

### GU24 CFL Type

Model	Input Voltage	Finish	Lamp	Shade	Dimension (H x W X E)	Energy Star
3-3383-05	120V	Black	GU24 Bulb	Opal Polycarbonate	11.3" x 7.0" x 3.7"	---