

# 3-4311

## Wall Mount, Outdoor



### Features

#### Housing

Die-formed Cold-rolled Steel with Powder Coated Finish  
 Finish Options: -05 Black, -06 White, -08 Gray

#### Electrical

120V, Built-in Photo Cell Option  
 High Power Factor, Low THD

#### Lamp


Integrate LED Module: More Color Temperature Option 3500K, 4000K, 5000K  
 GU24 LED Bulb Type: Color Temperature Option 3000K, 4000K  
 GU24 CFL Bulb Type: Color Temperature Option 2700K, 4000K

#### Certification

UL/cUL or ETL/cETL Listed, Suitable for Wet Locations

#### Warranty

5 Years Limited Warranty on Driver and LED



### LED Type

| Model                | Input Voltage | Input Wattage | LED CT/CRI  | Lumen (TYP) | Housing / Shade | Dimension (H x W X E) | Energy Star |
|----------------------|---------------|---------------|-------------|-------------|-----------------|-----------------------|-------------|
| 3-4311D-05-xxxxK     | 120V          | 15W           | 3000K / >80 | 1380        | Steel / Glass   | 9.1" x 6.7" x 4.4"    | Yes         |
| 3-4311D-05-xxxxK-11W | 120V          | 11W           | 3000K / >80 | 770         | Steel / Glass   | 9.1" x 6.7" x 4.4"    | Yes         |
| 3-4311D-05-L-xxxxK   | 120V          | 15W           | 3000K / >80 | 1380        | Steel / Glass   | 12.0" x 10.0" x 4.0"  | Yes         |

### GU24 Type

| Model         | Input Voltage | Finish | Lamp         | Shade         | Dimension (H x W X E) | Energy Star |
|---------------|---------------|--------|--------------|---------------|-----------------------|-------------|
| 3-4311-118-05 | 120V          | Black  | 1 x 18W GU24 | Frosted Glass | 9.1" x 6.7" x 4.4"    | ---         |