

DC331D DC333D DC335D DC336D



Ceiling Fixture

Features

Housing

Die-formed Cold-rolled Steel
 Finish Option: -62 Satin Nickel, -30 Oil Rubbed Bronze, -05 Black

Optical

Shade: High Transmission Acrylic Create Excellent Light Distribution and Uniformity

Electrical

High Power Factor, Low THD

Lamp

Built-in LED: High Efficiency, High CRI, Binned and Mixed to Reach Uniform Light
 Color Temperature Option – 3000K, 4000K

Certifications

ETL/cETL Listed, Suitable for Damp Locations

Warranty

5 Years Warranty on Driver and LED Module



LED Type

Model	Input Voltage	Input Voltage	Lumen (Typ) / CRI	CT	Finish	Shade	Dimension (OD X H)
DC336D-xxxxK-62	120V ~ 277V	17W	1100 / > 80	3000K or 4000K	Satin Nickel	Acrylic	14.0" x 2.5"
DC335D-xxxxK-62	120V ~ 277V	23W	1500 / > 80	3000K or 4000K	Satin Nickel	Acrylic	16.0" x 2.5"
DC333D-xxxxK-62	120V ~ 277V	35W	2300 / > 80	3000K or 4000K	Satin Nickel	Acrylic	18.0" x 2.5"
DC331D-xxxxK-62	120V ~ 277V	46W	2950 / > 80	3000K or 4000K	Satin Nickel	Acrylic	24.0" x 2.5"
DC336D-PD-xxxxK-62	120V ~ 277V	17W	1100 / > 80	3000K or 4000K	Satin Nickel	Acrylic	14.0" x 9.5"
DC335D-PD-xxxxK-62	120V ~ 277V	23W	1500 / > 80	3000K or 4000K	Satin Nickel	Acrylic	16.0" x 9.5"
DC333D-PD-xxxxK-62	120V ~ 277V	35W	2300 / > 80	3000K or 4000K	Satin Nickel	Acrylic	18.0" x 9.5"
DC331D-PD-xxxxK-62	120V ~ 277V	46W	2950 / > 80	3000K or 4000K	Satin Nickel	Acrylic	24.0" x 9.5"