

RT Series

LED Re-trofit Kits for Troffers



Features

Housing

Aluminum Extrusion Housing with Easy Mounting Bracket
Magnet Construction Makes Easy Pre-alignment on Installation

Optical

Shade: High Transmission Acrylic Creates Excellent Light Distribution and Uniformity

Lamp

Built-in LED Module, Color Temperature Option 4000K, 5000K

Certification

ETL/cETL Listed

Warranty

5 Years Warranty on Driver and LED Module



LED Re-trofit Kits

Model	Input Voltage	Input Wattage	Lumen (TYP) / CT	CRI	Dimension (L X W X H)
RT-2x2-2L-HO-xxxxK	120V ~ 277V	19W	1900 / 4000K	80	20.7" x 1.0" x 0.8"
RT-2x2-3L-HO-xxxxK	120V ~ 277V	29W	2820 / 4000K	80	20.7" x 1.0" x 0.8"
RT-2x4-2L-HO-xxxxK	120V ~ 277V	37W	3780 / 4000K	80	44.2" x 1.0" x 0.8"
RT-2x4-3L-HO-xxxxK	120V ~ 277V	55W	5620 / 4000K	80	44.2" x 1.0" x 0.8"
RT-2x2-2L-VHO-xxxxK	120V ~ 277V	16W	2050 / 4000K	80	20.7" x 1.0" x 0.8"
RT-2x2-3L-VHO-xxxxK	120V ~ 277V	23W	2950 / 4000K	80	20.7" x 1.0" x 0.8"
RT-2x4-2L-VHO-xxxxK	120V ~ 277V	30W	3960 / 4000K	80	44.2" x 1.0" x 0.8"
RT-2x4-3L-VHO-xxxxK	120V ~ 277V	44W	5780 / 4000K	80	44.2" x 1.0" x 0.8"